



TECHNICAL INFORMATION SHEET

SEAL-GUARD® GOLD LABEL IMPREGNATOR

PENETRATING SEALER FOR GROUT, TILE AND MASONRY

Applications: Suitable for all types of tile and masonry surfaces, including grout lines (damp/wet or dry), natural stone, sandstone, terracotta, stucco, concrete, brick, Saltillo tiles, porcelain stoneware, marble and granite. Seal-Guard® Gold Label Impregnator is suitable for both indoor and outdoor use.

Directions for use: Use as is. Try the product in an inconspicuous spot first to determine its suitability for the intended use. The surface must be clean and dry and free of wax, protective and finishing coats and grout haze. Cover paint or varnish next to the surface to be treated. Apply in a thin, even layer with a pressure sprayer, airless sprayer, brush, cloth, mop or roller.

One layer will usually be sufficient. However, on more porous surfaces, such as terracotta and sandstone, and on heavily trafficked surfaces, a second coat is recommended to ensure optimal protection. Wait at least twenty minutes before applying the second coat. Treated surfaces will take approximately 2.5 hours to dry and cure, but for optimal results they should be kept clean and dry for at least 24 hours.

Note: For highly polished surfaces, such as porcelain, marble or granite, a second coat is recommended. Buff small areas before the second coat is dry. Allow larger surfaces to dry and cure for 24 hours. If necessary, residue can be easily removed with a damp cloth.

Pre-grout sealer/Grout release: Ideal for use as a grout release prior to grouting, to prevent grout stains and make it easier to remove residue and grout haze.

Maintenance: Clean treated surfaces with water and a mild detergent. Aggressive cleaning agents such as scouring powders, ammonia, acids or bleach are unnecessary.

Life expectancy: If treated surfaces are cared for properly, Seal-Guard® will remain effective for many years. However, heavily trafficked surfaces should be checked annually and, if necessary, recoated.

Coverage: 1 litre will cover approximately 40 m², depending on the material to be treated and the application method used.

Specifications:

UN No. road transport:	1993
ADR class:	3, flammable liquid N.O.S. (heptane + acetone)
ADR packing group:	II
UN No. air transport:	1993
UN No. sea transport:	1993

Packaging: Available in 1-litre and 5-litre containers (12 x 1 litre per box) (4 x 5 litres per box).

Note: Do not use a sprayer with rubber parts that can come into contact with the impregnator.

Test data: The product claims regarding Seal-Guard® are supported by tests conducted by the Tile Council of America on staining, water vapour permeability, friction coefficients and use on damp grout. Test report number TCA-066-98. Test results available on request.



TECHNICAL INFORMATION SHEET

SEAL-GUARD® GOLD LABEL IMPREGNATOR

PENETRATING SEALER FOR GROUT, TILE AND MASONRY

Note: Please refer to the Safety Data Sheet for details on safe handling and required personal protective equipment.

The manufacturer/supplier is not liable for any direct or indirect consequences resulting from the incorrect application of its products. The only obligation of the manufacturer/supplier is to replace defective products. You are responsible for determining in advance whether a product is suitable for the intended use (at your own risk).

Manufactured by:
Seal-Guard Europe B.V.
Bakkerskamp 24
7582 HA Losser
The Netherlands

T +31 (0)53 5362127
info@seal-guard.eu
www.seal-guard.eu